



WNS Lowery
 2221 SE 69th St
 Oklahoma City, OK 73149
 (405) 677-7222

Flow and Pumping Tees

WNS Lowery offers a full line of Flow Tees and Pumping Tees ensuring we have the right thread combination for every application. Our Tees are precision machined to minimize any misalignment between the top and bottom threads. A 1" NPT bleeder port is available on all tees allowing the use of a pressure gauge or other equipment to be installed. Tees are available in 1500 psi, 3000 psi, or 5000 psi working pressure. When in harsh environments, a corrosion resistant coating is available to extend the life of the Flow and Pumping Tees.

Features:

- Precise Top/Bottom Thread Alignment
- 1500 psi, 3000 psi, & 5000 psi Working Pressures
- Numerous Thread Combinations Available, API and NPT
- Corrosion Resistant Coating Available
- 1" NPT Bleeder Optional
- NACE Optional



Applications:

- Artificial Lift Wells

Specifications:

Bottom Thread	Top Thread	Major Outlet	Bleeder Port (optional)
2", 2 1/2", 3" LP	2", 2 1/2", 3" LP	2", 2 1/2", 3" LP	1" LP
2 3/8", 2 7/8", 3 1/2" EUE	2 3/8", 2 7/8", 3 1/2" EUE	2 3/8", 2 7/8", 3 1/2" EUE	

*All standard combinations available